




环保物料



Specifications:

Voltage Rating : 125V AC/DC

Current Rating : 2A AC,DC

Withstand Voltage : 500V AC/minute

Contact Resistance : 30mΩ(MAX.)

Insulation Resistance : 1000MΩ(MIN.)

Temperature Range : -40°C~+70°C

Ordering Information & Specifications

Part No	Wire Range	Insulation O. D.	Material	Finish
42011TOP -**	AWG#30 -#24	0.8mm-1.4mm (1.4mm max)	Phosphor Bronze	Au or Sn

Unit: mm

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	康导新能源 网址: www.dgconne.com 电话: 0769-85387633 邮箱: 2850175986@qq.com 传真: 0769-85382827	PART. NO: 42011TOP-**
				LINEAR	ANGLES	APPROVED	黎腾	2017.06.16		DWG. NO: ENDE05
AO	新图面发行	2017.06.16	UNIT: MM	0.00±0.15	X° ±3°	DESIGNER	肖坤权	2017.06.16	TITLE: 2.00mm pitch Crimp Terminal	REV: AO SHEET: 1/1
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	旷淇	2017.06.16		