


环保物料



Specifications:  
 Voltage Rating : 250V AC/DC  
 Current Rating : 3A AC,DC  
 Withstand Voltage : 800V AC/minute  
 Contact Resistance : 10mΩ(MAX.)  
 Insulation Resistance : 1000MΩ(MIN.)  
 Temperature Range : -25°C~+85°C

<2 to 9 circuits>


<10,15 circuits>



Circuit No.1



Circuit No.1



Unit: mm

Part No.	Dimensions	
	A	B
2P	2.00	5.40
3P	4.00	7.40
4P	6.00	9.40
5P	8.00	11.40
6P	10.00	14.00
7P	12.00	16.00
8P	14.00	18.00
9P	16.00	20.00
10P	18.00	22.00
11P	20.00	24.00
12P	22.00	26.00
13P	24.00	28.00
14P	26.00	30.00
15P	28.00	32.00

Material	Color
PA66,UL94V-0	Gray

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE
				LINEAR	ANGLES			
			0.0±0.25	X° REF±6°	APPROVED	黎腾	2017.06.16	
A0	新图面发行	2017.06.16	UNIT: MM	0.00±0.15	X° ±3°	DESIGNER	肖坤权	2017.06.16
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.08	X° X'±2°	DRAWN	旷淇	2017.06.16



PART NO:	42005H00-NP*-66	
DWG. NO:	ENDE05	
REV:	A0	SHEET: 1/1

TITLE: 2.00mm pitch Single Housing