



# 环保物料

产品型号	MODEL	KD20H
材质&电镀	MATERIAL&PLATING	
螺丝	Screw	M5.0, 钢, 镀锌 steel, Zinc Plated
触点	Contact	铝 Aluminum
焊针	Pin header	磷青铜 Phosphor Bronze
塑件	Housing	Nylon PA66, UL94V-2
电气性能	ELECTRICAL	
额定电压	Rated voltage	500V
额定电流	Rated current	to EN60998:76A
接触电阻	Contact resistance	-
绝缘电阻	Insulation resistance	-
耐压	Withstanding voltage	-
使用线径	Wire range	6.0-16.0mm <sup>2</sup>
机械性能	MECHANICAL	
温度范围	Temp. range	-40℃~+110℃
瞬时温度	Max. soldering	KD20H
扭矩	Torque	H
剥线长度	Strip length	No. of pole 12pole



N=Number of Contacts

				GENERAL TOLERANCES		SCALE: 1:1	NAME	DATE	 <b>康导新能源</b> 网址: www.dgonne.com 电话: 0769-85337633 邮箱: 2850175886@qq.com 传真: 0769-85392827	PART. NO: KDTB0192
				LINEAR	ANGLES	APPROVED	黎腾	2017.06.16		DWG. NO:
A0	新图面发行	2017.06.16	UNIT: MM	0.00±0.25	X° ±3°	DESIGNER	肖坤权	2017.06.16	TITLE: Pitch11.00mm Feed Through Terminal Blocks	REV: A0
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.15	X° X'±2°	DRAWN	旷淇	2017.06.16		SHEET: 1/1