




环保物料



产品型号	MODEL	KD12EKD	
材质&电镀	MATERIAL&PLATING		
螺丝	Screw	-	
弹片	Reed	磷青铜 Phosphor Bronze	
焊针	Pin header	-	
塑件	Housing	PA66, UL94V-0	
电气性能	ELECTRICAL	UL	IEC
额定电压	Rated voltage	125V	130V
额定电流	Rated current	4A	10A
接触电阻	Contact resistance	20mΩ	
绝缘电阻	Insulation resistance	500MΩ/1000V	
耐电压	Withstanding voltage	AC1250V/1min	
使用线径	Wire range	28-20AWG 0.5mm ²	
机械性能	MECHANICAL		
温度范围	Temp. range	-40℃~+105℃	
瞬时温度	Max. soldering	+250℃, 5sec	
扭矩	Torque	-	
剥线长度	Strip length	8mm	



N=Number of Contacts

		GENERAL TOLERANCES		SCALE:	NAME	DATE	康导新能源 网址: www.dgoonne.com 电话: 0769-86337633 邮箱: 2860178888@qq.com 传真: 0769-86392827	PART. NO:	KDTB0062	
				1:1	黎腾	2017.06.16		DWG. NO:		
				APPROVED	肖坤权	2017.06.16			REV: A0	SHEET: 1/1
				DESIGNER	旷淇	2017.06.16		TITLE: Pitch2.50mm Pluggable Terminal Blocks		
AO	新图面发行	2017.06.16	UNIT: MM	0.00±0.25	X° ±3°					
REV.	REVISION RECORD	DATE	SIZE: A4	0.000±0.15	X° X'±2°					