






环保物料





主要技术参数 Main Specifications

线数 (Poles): 4 to 50
 接触电阻 (Contact resistance): $\leq 20m\Omega$
 绝缘电阻 (Insulation resistance): $\geq 100M\Omega$
 额定电压 (Rated voltage): 50V AC DC
 额定电流 (Rated current): 1.0A AC DC (AWG28#线)
 耐电压 (Withstand Voltage): 500V AC/minute
 温度范围 (Temperature Range): $-25^{\circ}C \sim +85^{\circ}C$



芯数	排列	A	B	C	D
4	2×2	1.0	4.3	2.5	表拉
6	2×3	2.0	5.3	3.5	
8	2×4	3.0	6.3	4.5	4.0
10	2×5	4.0	7.3	5.5	
12	2×6	5.0	8.3	6.5	7.0
16	2×8	7.0	10.3	8.5	
20	2×10	9.0	12.3	10.5	F
22	2×11	10.0	13.3	11.5	
24	2×12	11.0	14.3	12.5	F
28	2×14	13.0	16.3	14.5	
30	2×15	14.0	17.3	15.5	F
32	2×16	15.0	18.3	16.5	
36	2×18	17.0	20.3	18.5	F
40	2×20	19.0	22.3	20.5	
50	2×25	24.0	27.3	25.5	F



ITEM	COMPONENT	Q'TY	MATERIAL	FINISH
5	MYLAR	1 PCS		
4	CAP	1 PCS	PA9T	UL 94V-0, COLOR:BEIGE
3	SOLDER TAB	2 PCS	Barss	Sn plated
2	CONTACT	4~50 PCS	PhosphorBronze	Gold/Sn plated
1	HOUSING	1 PCS	PA9T	UL 94V-0, COLOR:BEIGE

REV.		REVISION RECORD	DATE	UNIT: MM	SIZE: A4	GENERAL TOLERANCES	SCALE: 1:1	NAME	DATE	康导新能源 网址: www.dgonne.com 电话: 0769-85337633 邮箱: 2850175988@qq.com 传真: 0769-85392827	PART. NO: 21006AWV	DWG. NO:	REV: A0	SHEET: 1/1
						LINEAR	ANGLES	APPROVED						
						0.00±0.25	X° ±3°	DESIGNER						
						0.000±0.15	X° X'±2°	DRAWN						
AO		新图面发行	2017.06.16	MM	A4	0.00±0.35	X° REF±6°	黎腾	2017.06.16	TITLE: 1.0mmPITCH 180° WAFER SMT TYPE				