





# 环保物料

Pin数	尺寸A	尺寸B
2×1	4.70	-
2×2	8.90	4.20
2×3	13.10	8.40
2×4	17.30	12.60
2×5	21.50	16.80
2×6	25.70	21.00
2×7	29.90	25.20
2×8	34.10	29.40
2×9	38.30	33.60
2×10	42.50	37.80
2×11	46.70	42.00
2×12	50.90	46.20
2×13	55.10	50.40
2×14	59.30	54.60
2×15	63.50	58.80
2×16	67.70	63.00
2×17	71.90	67.20
2×18	76.10	71.40
2×19	80.30	75.60
2×20	84.50	79.80



PCB LAYOUT

Specification:  
 Current Rating : 7AMP  
 Temperature Range : -40°Cto+105°C  
 Contact Resistance : 20mΩ Max  
 Insulation Resistance : 1000MΩ Min  
 Withstanding Voltage : AC 1000V  
 Material:  
 Insulator : Polyester (UL94V-0)  
 Standard:PA9T/PBT  
 Contact: Brass  
 Plating : Au or Sn Over 50u" Ni

		GENERAL TOLERANCES		SCALE:	NAME	DATE	康导新能源	PART. NO:
		LINEAR	ANGLES	1:1	黎腾	2022. 11. 3		KDPH-0129
				APPROVED	肖坤权	2022. 11. 3	康导新能源 网址: www.dgconne.com 电话: 0769-85337633 邮箱: 2850175986@qq.com 传真: 0769-85392827	DWG. NO:
A0	新图面发行	2022. 11. 3	UNIT: MM	DESIGNER	肖坤权	2022. 11. 3		ENDE0129
REV.	REVISION RECORD	DATE	SIZE: A4	DRAWN	黄薇	2022. 11. 3	TITLE: Pitch4.20mm Pin Header, Dual Plastic, Dual Row, Right Angel Type	REV: A0 SHEET: 1/1